

# Bermuda LX View

H 134

P 81

L 134 (10) • 167 (13)

Gelato

TN	TB	TB/TN	TC	TC/TN	N
Chiller	Freezer	Dual Temp	Heated	Hot&Cold	Non-refrigerated

RS - Static					
RV - Ventilated	•				
RS/TC S - Static and Dry Heat convertible					
RV/TC S - Ventilated / Dry Heat convertible					
HUR - Meat					
CH - Chocolate					
TC S - Dry Heat					
TC BM - Bainmarie					
N - Non-refrigerated					

**Installation**  
Plug-in

**Temperature**  
-16/-14 °C

**Refrigerant**  
R290

**Refrigeration**  
Ventilated

**Compressor**  
Hermetic

**Defrost**  
Hot gas

**Climate class**  
7

**Upper class**  
Tempered

**Front glass**  
Heated

**Side glass**  
Tempered

**Front opening system**  
Openable glass structure towards the bottom

**Rear closing system**  
Self-rolling curtain

**Work top**  
Prepainted sheet  
Grey RAL 9006

**Lighting**  
Led 5700 K

**Equipment handling**  
Swivel casters with brake

**Storage cell**  
Static refrigerated  
with skin evaporator

**Installazione**  
Plug-in

**Temperatura**  
-16/-14 °C

**Refrigerante**  
R290

**Refrigerazione**  
Ventilata

**Compressore**  
Ermetico

**Sbrinamento**  
Gas caldo

**Classe climatica**  
7

**Vetro superiore**  
Temperato

**Vetro frontale**  
Riscaldato

**Vetri laterali**  
Temperato

**Apertura anteriore**  
Ribaltabile manualmente verso il basso

**Chiusura posteriore**  
Tenda manuale autoavvolgente

**Piano di servizio**  
Lamiera preverniciata  
Grigio RAL 9006

**Illuminazione**  
Led 5700 K

**Movimentazione**  
Ruote pivotanti con freno

**Cella di riserva**  
Refrigerata statica con evaporatore a mantello



R290



Available colours - Colori disponibili

**Internal**

Interno



White

**Front**

Frontale



White

**Sides**

Fianchi



White

Height Altezza	Length Lunghezza	Model type Tipo di banco	Total display area Superficie espositiva totale m <sup>2</sup>	Temperature class Classe di temperatura	Recommended temperature Temperatura consigliata °C	Energy class Classe energetica	Energy efficiency index Indice di efficienza energetica EEI	Annual energy consumption Consumo annuo AEC kWh/A	Light source type and class Tipo e classe illuminazione
H134	134	IGF2	0,65	G2	-15°C	E	50,4	8.213	-
	167	IGF2	0,84	G2	-15°C	D	45,1	8.322	-

**Configuration: air cooled plug in unit R290, self-rolling curtain closure, led lighting.**

Configurazione: motore a bordo ad aria R290, chiusura tenda manuale autoavvolgente, illuminazione led.

## Bermuda LX View

10	13
RV TB	RV TB

<b>External dimensions (LxDxH)</b> Dimensioni esterne (LxPxH)	1340 x 814 x 1354 mm	1670 x 814 x 1354 mm
<b>Capacity (gross / net)</b> Capacità (lorda / netta)	300 / 255 Lt	395 / 325 Lt
<b>Weight (net)</b> Peso (netto)	195 kg	235 kg
<b>Refrigeration</b> Refrigerazione	<b>Ventilated</b> Ventilata	
<b>Refrigerant</b> Refrigerante	R290	
<b>Climate class</b> Classe climatica	7	
<b>Operating conditions</b> Condizioni ambientali	35 °C / 75 %RH	
<b>Product temperature</b> Temperatura prodotto	-16/ -14 °C	
<b>Compressor (q.ty - type)</b> Compressore (q.tà - tipologia)	<b>2 - Hermetics</b> 2 - Ermetici	
<b>Defrost</b> Sbrinamento	<b>Hot gas</b> Gas caldo	
<b>Power supply</b> Alimentazione	230 V / 1 Ph / 50 Hz	
<b>Electrical input (nominal)</b> Assorbimento elettrico (regime)	1250 W / 5,8 A	1600 W / 8 A
<b>Electrical input (defrost)</b> Assorbimento elettrico (sbrinamento)	1360 W / 6,6 A	2000 W / 10 A

Technical sheet about models whit condensing unit included with air cooled  
Dati tecnici riferiti a modelli con unità a bordo con condensazione ad aria

### Item

Accessorio







<b>White cone holder</b> Portaconi completo bianco	•	•
<b>Scoop washer with stainless steel container</b> Lavaporzionatore vaschetta inox	•	•



Storage cell  
Cella di riserva

### Setup - Stainless steel containers

Allestimento - Vaschette gelato in Acciaio Inox

<b>Display</b> Vasca espositiva	<b>5 Lt</b> 360 x 165 x 120 h		10	13
	<b>5 Lt</b> 360 x 250 x 80 h		6	8
	<b>10 Lt</b> 360 x 250 x 120 h		6	8
<b>Storage cell</b> Cella di riserva	<b>5 Lt</b> 360 x 165 x 120 h		4 + (4)	6 + (6)
	<b>5 Lt</b> 360 x 250 x 80 h		2 + (3)	2 + (2)
	<b>10 Lt</b> 360 x 250 x 120 h		2 + (3)	2 + (2)

